



WATERTIGHT METAL ACCESSORY
(eg. EQUIPMENT CURBS, PIPE
FLASHINGS, ETC.)

2 PLYS POLY-FELT 125VP SET
IN AND TOP COATED WITH
RAM-TOUGH 250 BITUMEN

RAM METAL EDGING (OPTIONAL)

OVERBURDEN
INSULATION, PAVERS, BALLAST.
GREENROOF-ROOFSCAPES®

POLY-FELT FILTER FABRIC 3.5

APPROVED MECHANICAL
FASTENERS 6" O.C.

3" MIN FLANGE
LEG
6" MIN
OVERLAP

SPECIFIED PROTECTION COURSE
SET IN TOP COAT OF RT 250
BITUMEN

PRIMED CONCRETE DECK

RAM-TOUGH 250DM MONOLITHIC MEMBRANE

RT 250 BITUMEN - 125 MILS (MIN.) (APPROX, 1 LB/SQ.FT.)
POLY-FELT 125VP REINFORCEMENT (1 PLY-2" SIDE LAP/6" END LAP)
RT 250 BITUMEN - 90 MILS (MIN.) (APPROX 0.7LBS/SQ.FT.)



Between the World
and The Weather
Since 1928

Greenroof-Roofscapes®

RAM-TOUGH 250
HEAVY DUTY STRIP FLASHING
(DRAWING NOT TO SCALE)

DATE ISSUED:

08/09

DRAWING NUMBER:

RT250-45