

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: RAM•MASTIC

HMIS CODES: H F R P
 0 0 0

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME:	Barrett Company, Inc.	EMERGENCY PHONE:	(800) 647-0100
ADDRESS:	33 Stone House Road	INFORMATION PHONE:	(908) 647-0100
	P.O. Box 421		
	Millington, New Jersey 07946-0421	DATE PREPARED:	August 1, 1991

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS Specify Chemical Identity; Common Names	CAS Number	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE		WEIGHT %
		OSHA PEL	ACGIH TLV	Other	as Hg @ TEMP		
Styrene-Butadiene Block Copolymer	9003-55-8	N/A	N/A	N/A	N/A		
Aromatic Solvent	64742-95-6	100 PPM	100 PPM	N/AS	2.7	68°F	
Zinc Dibutyldithiocarbamate	136-23-2	N/A	N/A	N/A	N/A		
UV Absorber	25973-55-1	N/A	N/A	N/A	N/A		
UV Absorber	52829-07-9	N/A	N/A	.1 MG/M ³	N/A		
*Xylene	1330-20-7	100 PPM	100 PPM	N/A	6.6	68°F	1
Carbon Black	133-86-4	3.5 MG/M ³	3.5 MG/M ³	N/A	N/A		
Hydrocarbon Resin	68003-51-0	N/A	N/A	N/A	N/A		
Asphalt	8052-42-4	5 MG/M ³	5 MG/M ³	N/A	N/A		
Organophilic Clay	121888-67-3	15 MG/M ³	15 MG/M ³	N/A	0.1	68°F	
Silicone Dioxide	7631-86-9	20 MPPCF	10 MG/M ³	N/A	N/A		
Amorphous Glass Fiber Trade Secret	N/A	N/A	N/A	N/A	N/A		

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE:	282°-900°F	SPECIFIC GRAVITY (H ₂ O = 1)	1.0
VAPOR DENSITY:	Heavier than air.	EVAPORATION RATE:	Slower than ether.
COATING V.O.C.:	2.75 lb/gal (330 gal)		
SOLUBILITY IN WATER:	Negligible		
APPEARANCE AND ODOR:	Black paste, mild solvent odor.		

MATERIAL SAFETY DATA SHEET
RAM MASTIC / SURFACE CONDITIONER (Continued)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition, ventilate areas. Remove with inert absorbent and non-sparking tools.

WASTE DISPOSAL METHOD: Incinerate under safe conditions or dispose of in accordance with Local, State and Federal Regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not breathe vapors, use with adequate ventilation. Do not take internally. Do not get in eyes. Wear impervious clothing. Keep away from heat and flame.

OTHER PRECAUTIONS: Never use welding or cutting torch on or near container because product can ignite explosively.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: Respirator in confined area.

VENTILATION: Local exhaust recommended.

PROTECTIVE GLOVES: Normal work gloves.

EYE PROTECTION: Safety glasses or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye bath and safety shower.

WORK/HYGIENIC PRACTICES: Wash hands before eating or using restroom. Smoke only in approved areas.

SECTION IX - DISCLAIMER

Information presented herein has been compiled from sources to be dependable and is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. It is the users responsibility to determine for itself the suitability of any material for a specific purpose, whether alone or in combination with any other products and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions and methods of use are not under our control, we must necessarily disclaim all warranties of merchantability or fitness for any particular use as well as all liability resulting directly or indirectly from the use of any materials supplied by us. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation.