

ram Primer/Surface Conditioner

PRODUCT DESCRIPTION

General purpose asphalt primer for hot or cold bitumen coatings. Brush or spray application. Complies with Federal Specifications SS-A-701, ASTM D-41 and AASHTO M-116.

USES

Ram Primer is designed for use as a general utility prime coat for concrete, gypsum, masonry, brick and metal surfaces over which asphaltic waterproofing, dampproofing, roof coatings and other asphaltic products are to be applied. This thin solution readily penetrates pores and seals residual dust of concrete and masonry surfaces providing a base for asphalt based coatings. Ram Primer is specified as a prime coat for the application of ram-Tough membranes. It is also used as a felt primer on old dried out built-up roofs before roof coatings are applied.

APPLICATION

All surfaces to be primed with **ram** Primer/Surface Conditioner must be dry and free from surface moisture, rust, dust, dirt, oil, grease and any other foreign matter.

Easily applied by brush or spray equipment at a rate of 1 to 2 gallons per 300/500 Sq. Ft. depending upon the porosity and type of surface being primed.

Brushes and other tools may be thoroughly cleaned after use with mineral spirits, taking the necessary precautions when handling combustible materials.

CAUTION

ram Primer/Surface Conditioner should not be used near open flame. Adequate ventilation must be provided. Drying time will vary with temperature, sunlight, humidity and thickness of application.

Physical Properties

<u>Test</u>	<u>Method</u>	<u>Typical Results</u>
Asbestos Content	ASTM-D-276	0

(Cont'd over)

Density @ 77°F	ASTM-D-1475	7.4 lb/gal
Solids by Weight	ASTM-D-1644	47.8%
Flash Point	ASTM-D-3278	> 100°F

Available in 5 gallon pails (weight 42 lbs) and 55 gallon drums (weight 465 lbs).