



Between the World
and The Weather
Since 1928

Poly•Felt 3.5 Filter Fabric

PRODUCT DESCRIPTION

Poly•Felt 3.5 Filter Fabric is a lightweight spunbond polyester geotextile fabric. Its continuous filament spunbond manufacturing process provides excellent strength-to-weight ratio.

USES

- Typically used as an insulation overlay in a Protected Roof Membrane Assembly, Poly•Felt 3.5 Filter Fabric helps protect against:
 - UV deterioration of the insulation
 - Ballast entering the insulation joints
 - Insulation displacement due to floatation
 - Improves wind up-lift characteristics by more evenly distributing overburden weight.
- Used in greenroof or planter applications, Poly•Felt 3.5 Filter Fabric helps prevent the growing media from washing into the insulation joints and potentially clogging the drainage system.

FEATURES

- Lightweight
- High tensile strength
- High puncture and tear resistance
- Larger roll sizes

BENEFITS

- Easy installation reduces application time
- Superior durability
- Cost effective
- Proven performance

PACKAGING

Length 360 ft.
Width 12.5 ft.
Roll Size (area) 4500 sq.ft.

APPLICATION GUIDELINES

- All laps should be a minimum of 12 inches
- Turn up above overburden at perimeters
- Fasten or ballast immediately after installation
- After overburden installation, cut off protruding fabric at perimeters



TYPICAL PHYSICAL PROPERTIES

Properties	Method	Typical Results
Fabric Weight	ASTM D-1117	3.5 (oz./sq.yd.)
Elongation	ASTM D-4632	50 (%)
Trapezoid Tear	ASTM D-4533	40 (lbs)
Tensile Strength	ASTM D-4632	90 (lbs)
Mullen Bursting	ASTM D-3786	185 (psi)
Puncture Strength	ASTM D-4833	60 (lbs)
Permeability	ASTM D-4491	0.2 (cm/sec)
Permittivity	ASTM D-4491	2.2 (1sec.)
Water Flow Rate	ASTM D-4491	150 (g/m/sf)

APPLICATION PRECAUTIONS

- Store in dry protected location
- Do not expose to open flames
- **READ MATERIAL SAFETY DATA SHEET BEFORE USING**
- **FOR PROFESSIONAL CONTRACTORS USE ONLY.**

PRODUCT SAFETY INFORMATION

Poly-Felt 3.5 Filter Fabric offers no unusual health or safety risks for a product of this nature. As with any roofing process, proper ventilation, clothing and eye protection is important.

For specific information, contact the Barrett Company for a current Material Safety Data Sheet on this product.

The user should not assume that all safety measures are indicated or that other measures may not be required.

Note

All statements, information and data given herein are believed to be accurate and reliable, but are presented without guaranty, warranty or responsibility of any kind, expressed or implied, except as may be indicated herein. Statements or suggestions concerning possible uses of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent.

Issued 8/10