

BARRETT ram-TOUGH 250 WATERPROOFING PRIMARY PRODUCT LIST

Membrane Components

ram-Tough 250 - a hot applied waterproofing membrane composed of Kraton® SBS rubber polymers and specially refined asphalts, blended with an inert mineral filler. Forms a monolithic, joint free membrane on horizontal or vertical surfaces. Requires a double-jacketed melter to heat material.

POLY•FELT 125VP - a polyester reinforcement for ram-Tough 250 membrane.

Flashing Material

ram 327 HDR - a heavy duty uncured neoprene rubber reinforcing sheet, 60 mils thick.

ram 306 - SBS modified flashing sheet, polyester reinforced, granule surfaced, 4mm thick.

Protection Course

ram 200 - SBS modified protection course sheet, polyester reinforced, smooth surfaced, 3mm thick.

ram 201 - SBS modified protection course sheet, fiberglass reinforced, smooth surfaced, 1mm thick.

ram 203 - SBS modified protection course sheet, fiberglass reinforced, smooth surfaced, 2.2mm thick.

Accessories

ram Primer/Surface Conditioner – asphalt based primer meeting ASTM D-41

ram Mastic – cold applied, trowel grade, SBS rubberized mastic for miscellaneous repair.

For specialty or custom blended products not shown here contact Barrett Technical Services.