

Greenroof-Roofscapes® | Westile®

Wood Plaza Pavers



DESCRIPTION

Wood Plaza Pavers are an untreated, low maintenance, natural product made from either Cumaru or Ipe wood. Both Cumaru and Ipe are known for their high density, strength, durability and resistance to decay and insects. Depending on climatic conditions, Wood Plaza Pavers will develop an aged patina and faded coloring as they age. The ends of the wood tiles are sealed with wax at the factory to prevent splitting. Additional cuts made in the field should be sealed. Wax on ends can bleed into wood and be visible, but should become less noticeable over time.

DIMENSIONS

23.88" x 23.88" x 2.69" (nominal)
23.88" x 47.88" x 1.69" (nominal)

WEIGHT

5.56 lbs. per square foot

SURFACE

Smooth

FIRE RATING


Class A (ASTM E108-07a Spread of Flame)

JANKA HARDNESS RATING

Ipe = 3,680 lbf
Cumaru = 3,540 lbf
Massaranduba = 3,190 lbf

COLORS

Natural variations to be expected



Ipe



Cumaru

FSC® Certified Available (FSC-C131838)

Cleaning, Sealing, Staining:

If desired, Wood Pavers can be periodically cleaned, stained and sealed. Before applying any finish, first clean and remove any residue or excess wax from the wood paver. The following manufacturers offer products specifically designed for use with tropical hardwoods: Cabots, Penofin, Messmers.



WESTILE®

DOCUMENT: KF-07014 - 1



(800) 647-0100



info@barrettroofs.com

barrettroofs.com