

PolyFelt 3.5

Protective Insulation Filter Fabric



Description

PolyFelt 3.5 is a lightweight continuous spunbond filament polyester geotextile fabric that provides excellent strength to weight ratio.

Uses

Install on the insulation to protect it from UV degradation, ballast and growing medium entering the joints and potentially clogging drain.

Coverage

4,050 sq ft per roll

Applications

Should be overlapped a minimum of 12", turn up above overburden at all perimeters and fasten immediately after installation. Any protruding fabric after overburden has been installed should be removed.

Properties

Description	Measurement	Test Method
Fabric Weight	3.5 oz./sq.yd.	
Elongation	50%	ASTM D-4632
Trapezoid Tear	40 lbs	ASTM D-4533
Tensile Strength	90 lbs	ASTM D-4632
Mullen Bursting	185 psi	ASTM D-3786
Puncture Strength	60 lbs	ASTM D-4833
Permeability	0.2 cm/sec	ASTM D-4491
Permittivity	2.2 1sec.	ASTM D-4491
Water Flow Rate	150 g/m/sf	ASTM D-4491



12.5"x360' Loose shipped
Roll Weight 110 lbs

LIMITED WARRANTY: Barrett warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Barrett makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to The Barrett Company, LLC. Barrett to replace or to refund the purchase price of the quantity of Barrett proven to be defective, and Barrett shall not be liable for any loss or damage.

20.1
Document: KF-01015



800 | 647 | 0100
F 908 | 647 | 0278