

# Ram Primer & Surface Conditioner



## Asphalt Based Surface Conditioner

### Description

Ram Primer & Surface Conditioner is a general utility asphaltic prime coat for porous and non-porous surface for application of RamTough 250 and RamTough KLB-100.

### Uses

Prepares concrete, gypsum, brick, masonry, metal and aged asphalt roofing membrane to be coated with RamTough 250 and RamTough KLB-100.

### Coverage

All surfaces to be primed with Ram Primer & Surface Conditioner must be clean, dry and free from moisture, rust, dust, dirt, oil, grease and any other foreign matter.

- Brush/Roller Application rate is 100-300 sq ft / gal.
- Spray Application rate is 300-500 sq ft /gal.

*Note: Application rates due vary pending the porosity of substrate.*



### Properties

Description	Test Method	Value
Color		Black
Flash Point (°F)	ASTM D-3278	>100°F (37.78°C)
Density @ 77°F	ASTM D-1475	7.4lb/gal (7.89kg/3.785 L)
Solids by Weight	ASTM D-1644	47.8%
Asbestos Content	ASTM D-276	0

**PLEASE NOTE:** Ram Primer & Surface Conditioner conforms to ASTM D-41 standards as an asphaltic primer suitable for use with asphalt in roofing, dampproofing, and waterproofing below or above ground level, for application to concrete, masonry, metal, and asphalt surfaces.

### Packaging

5 gallon pails  
42 lbs/pail  
36 pails/pallet

**LIMITED WARRANTY:** Barrett warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Barrett makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to The Barrett Company, LLC. Barrett to replace or to refund the purchase price of the quantity of Barrett proven to be defective, and Barrett shall not be liable for any loss or damage.

22.1  
Document: KF-01009



800 | 647 | 0100  
F 908 | 647 | 0278

