

Ram 200

Modified Bitumen Heavy-Duty Protection Course



Description

Ram 200 is a polyester reinforced, SBS modified bitumen membrane with sanded surfaces. The high-strength polyester reinforcement gives the composite membrane excellent tensile strength, toughness, puncture and tear resistance to create a heavy-duty protection course.

Uses

Ram 200 can be used as a heavy-duty protection course for RamTough 250 and RamTough KLB-100 applications.

Coverage

107 sq ft



Properties

Description	Measurement	Test Method
Thickness	3.0 mm (118 mils)	
Max Load @ 0°F (-17.78°C)	98 lbf/in (17.15 kN/m)	
Elongation @ 0°F (-17.78°C)	29%	ASTM D-4632
Max Load @ 0°F (23.89°C)	63 lbf/in (11.025 kN/m)	
Elongation @ 0°F (23.89°C)	29%	ASTM D-4632
Tear Strength @ 0°F (23.89°C)	87 lbf (15.23 kN/m)	
Low Temperature Flex	-15°F (-26.11°C)	
Dimensional Stability	< 0.5 % (max)	



Packaging

39"x 33'
80 lbs. per roll
30 per pallet

LIMITED WARRANTY: Barrett warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Barrett makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to The Barrett Company, LLC. Barrett to replace or to refund the purchase price of the quantity of Barrett proven to be defective, and Barrett shall not be liable for any loss or damage.

20.1
Document: KF-01016



800 | 647 | 0100
F 908 | 647 | 0278