

Ram RB 30

30 Mil Root Barrier



Description

RAM RB 30 is a 30-mil polymeric sheet, effectively arrests root penetration and redirect roots to a horizontal growth plane, helping lock in vegetation and increasing resistance to wind up-lift forces.

Uses

Ram RB 30 direct roots into a horizontal plane away from waterproofing, prevent root damage to the waterproofing membrane and prevent root intrusion into Green Roof and planter applications.

Coverage

773 sq ft

Application Guidelines

All laps should be a minimum of 12 inches. Turn up minimum 4 inches above finish elevation line at perimeters and projections and temporarily tape to the walls. Tape all seams with Barrett Ram RB 25 Seam Tape. Repair punctures and any other damages before installing drainage mat.



Properties

Description	Measurement	Test Method
Thickness	30 mils	ASTM D-5119
Weight	13.98 lbs/100 sq. ft. approx	
Tensile Strength at break	144 ppi	ASTM D-6693
Elongation@Break*	900%	ASTM D-6693
Tear Resistance	18 lbs	ASTM D-1004
Puncture Resistance	60 lbs	ASTM D-4833
Oxidation Induction Time	100 min	ASTM D-3895
Carbon Black	2.4%	ASTM D-4218
2% Secant Modulus	30,000 psi (max)	ASTM D-5323
Hydraulic Conductivity	2.5×10^{-10} cm/sec	
Static Use Temperature	Max 180°F Min -70°F	



Packaging

53"x175'
115 lbs. per roll
9 rolls per pallet

LIMITED WARRANTY: Barrett warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Barrett makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to The Barrett Company, LLC. Barrett to replace or to refund the purchase price of the quantity of Barrett proven to be defective, and Barrett shall not be liable for any loss or damage.

20.3

Document: KF-01023



800 | 647 | 0100
F 908 | 647 | 0278