

Greenroof-Roofscapes®

SpiralJack Adjustable Pedestals & Components



DESCRIPTION

Vegetated roofs have different depths, necessitating a flexible pedestal system that can support differing heights. Barrett's Greenroof-Roofscapes® SpiralJack Pedestal system:

- Has a **height range from 5/64" - 42 5/8"** for use with concrete, wood, porcelain, and stone pavers or tiles
- Features **slope correction up to 4%**
- Meets **all necessary spacing sizes**, dependant on your paver size and spacing requirements
- Provides **flexibility**; all components & accessories are easily inserted or removed from the pedestal
- Does not penetrate or compromise waterproofing membranes due to its **large flat base** and **rounded edges**



PACKAGING

- Full Box
- 20 Boxes per Pallet

TECHNICAL PROPERTIES

PROPERTIES	MEASUREMENT	TEST METHOD
Materials	Recycled Polypropylene (resistant to mold, alkali, and bitumen)	—
Base Diameter	7 43/64" (195mm)	—
Height Range	5/64" - 42 5/8" (2mm - 1083mm)	—
Slope Correction	0 - 4%	—
Spacer Tab Thickness	1/8" (3mm) 5/32" (4mm) 3/16" (5mm)	—
Compressive Resistance	1,984 lbs. minimum	—
Standard Kit	• Pedestal Base • Pedestal Top • PPC-TSP Spacer Tab • PPC-SHM-2 Neoprene Shims	
Additional Components	• PPC-EXT Adjustable Heights Extender • PPC-TSC Top Slope Corrector • PPC-BSC Bottom Slope Corrector • PPC-BCL Bearer Holder • PPC-WUA-B Basic Wind Uplift Assembly • PPC-WUA-C Concealed Wind Uplift Assembly	



(800) 647-0100




info@barrettroofs.com

barrettroofs.com




Spacer Tab
312-PPC-TSP




Neoprene Shims
312-PPC-SHM-2




Adjustable Height Extender
312-PPC-EXT



Top Slope Corrector
312-PPC-TSC*




Bottom Slope Corrector
312-PPC-BSC*



Bearer Holder
312-PPC-BCL*



Basic Wind Uplift Assembly
312-PPC-WUA-B*



Concealed Wind Uplift Assembly
312-PPC-WUA-C*




5/64" (2 mm)
311-PPE-2



1/4" (7 mm)
311-PPE-7



1/2" (13 mm)
311-PPE-13



5/8" (16 mm)
311-PPE-16



3/4"-1"
(18-25 mm)
311-PPE-18



1"-1 1/2"
(28-40 mm)
311-PPE-28



1 1/2"-2"
(36-51 mm)
311-PPE-36



2"-3 1/4"
(52-82 mm)
311-PPE-52



3 1/4"-5 1/4"
(82-135 mm)
311-PPE-82



5 1/4"-8 7/8"
(133-225 mm)
311-PPE-133



7 1/2"-11 1/2"
(189-293 mm)
311-PPE-189



10 1/4"-14 3/8"
(260-365 mm)
311-PPE-260



14 3/8"-20"
(364-507 mm)
311-PPE-364



18 1/2"-25 5/8"
(471-651 mm)
311-PPE-471



22 5/8"-31 1/4"
(576-795 mm)
311-PPE-576



26 7/8"-37"
(682-939 mm)
311-PPE-682



31"-42 5/8"
(786-1083 mm)
311-PPE-786

