Greenroof-Roofscapes®

Flex Line Concrete Pavers



DESCRIPTION

Greenroof-Roofscapes® Flex Line Concrete Pavers are hydraulically pressed to superior European standards. Suitable for use in a diverse range of applications and design needs, these pavers offer many advantages:

- **high compressive strength** and durability comparable to stone, thanks to its unique manufacturing process.
- Stylish and strong, these pavers are superior to conventional concrete pavers in appearance and performance.
- Ideal for heavy traffic applications.
- Available in a wide variety of paver sizes, colors, designs, and textures to accent any building, decor, or landscaping.
- System provides a uniform and even spacing and can accomodate custom designs to fit special paving patterns



LEED INFORMATION

- Sustainable Sites (SS)
- Materials & Resources (MR)



PACKAGING

- 88 sq/ft per Pallet (Full Pallet)
- 22 Pallets per Load (Full Load)
- * Special Order Product



	PROPERTIES	MEASUREMENT	TEST METHOD
TECHNICAL PROPERTIES	Dimensions	11 ^{3/4} " x 23 ^{1/2} " x 2" 17 ^{5/8} " x 17 ^{5/8} " x 2" 23 ^{7/8} " x 23 ^{7/8} " x 2" 35 ^{7/8} " x 23 ^{7/8} " x 2" 47 ^{7/8} " x 23 ^{7/8} " x 2 ^{1/2} "	FCP-SC-12/24 FCP-SC-18/18 FCP-SC-24/24 FCP-SC-36/24 FCP-SC-48/24
	Weight	23 lbs/sq ft	-
	Compressive Strength	9,705 - 11,385 lbs/sq in	-
	Water Absorption	< 3.5 - 3.6%	ASTM C-140
	Freeze-Thaw Durability	< 0.8 - 1.0%	ASTM C-1262
	Coefficient of Friction	0.70 - 0.74 (wet) 0.80 - 0.84 (dry)	ASTM C-1028-89
	Stain Resistance	Class 5	ISO 10545-14
	Fire Rating	Class A	-
	Building Strength/ Breaking Load	Class 14	-
	Abrasion Resistance	9.5 cm³ / cm² (50%)	ASTM C-418



(800) 647-0100



Quarry Stone Finish





(800) 647-0100

Slate



info@barrettroofs.com

Diamond

barrettroofs.com

Slotted

DOCUMENT: KF-07024 - 1

ADA Compliant