THE ROOFSCAPES ABS INSPECTION CHAMBER

The Roofscapes ABS Inspection Chamber is designed for vegetative roofs requiring rapid water drainage.

Specific to this product, it:

- **protects the outlets** from severe external effects
- incorporates **drainage slots on all sides** that retain growth media while allowing water to flow freely through
- also available is an **easily removable cover** to allow access for inspection and for simple maintenance to remove any excess debris





LEED Credits available for:

• Materials & Resources (MR)



- Individual Unit
- Full Carton
- Full Pallet



- 6 Units per Carton
- 16 Cartons per Pallet (96 Units)

TECHNICAL DATA

Materials:

UV Resistant Recycled ABS Plastic

Inspection Chamber Dimensions (W x L):

- 14.5" x 14.5" (shaft)
- 18.5" x 18.5" (base)

Inspection Chamber Height:

- 4.33" minimum
- Height adjustable in 4" segments
- Maximum Height of 32"

Inspection Chamber Weight:

• 5.3 lbs. / unit

Shaft Floor Opening:

11 3/4"

Water Discharge Capacity (each system):

- at 0% Slope = 17.91 gallons / minute
- at 2% Slope = 19.65 gallons / minute
- at 3% Slope = 19.81 gallons / minute

*dependent on media type

Compressive Strength:

330 lbs.

Vegetated Roofing Use:

Ancillary drainage component for use as a roof outlet inspection on vegetated roofs

