

# ROOFSCAPES®

# SpinOut®

## Root Growth Regulator



**SePRO Corporation**  
11550 North Meridian Street, Suite 600  
Carmel, IN 46032, U.S.A.

### Description

SpinOut® Root Growth Regulator is a water-based, latex coating that acts as a root pruning agent to control root spiraling and promote the development of a fibrous root system in Roofscapes® green and vegetative roof assemblies.

SpinOut® is designed to be spray, brush, or roller applied to all sheet lap edges of Barrett's Terra-BARRIER™ RB root barriers when used to divert plant roots around or under structures like sidewalks, retaining walls, street curbs, and building foundations.

### Benefits

- Prevents root circling/matting
- Eliminates the need for root pruning
- Can be used on many surfaces including plastic and fabrics
- Saves money by reducing plant replacement costs
- Increases the plants ability to absorb water and nutrients
- Increases transplant survivability; Roots remain healthy and begin growing immediately upon transplant
- Versatile root growth control in various settings around the growing facility

### Installation

All laps between sheets of Terra-BARRIER™ RB must either be sealed with a Roofscapes® waterproofing membrane or sealed with a propane torch (using standard APP torching application techniques) prior to treatment of exposed edges with SpinOut®.

Combine 1 gallon of SpinOut® and 2 quarts of water in the sprayer and shake or stir to thoroughly mix the contents before and during use. Adjust the spray tip to a wide fan spray and test the application, adjusting the orifice to provide a consistent application.

Hand pump spray equipment typically comes with detailed instructions on setup, operation, clean up, and maintenance. When referring to these instructions, SpinOut® is the equivalent of a flat, water-based latex paint. Therefore, use the largest orifice spray tip supplied with the sprayer.

### Properties

Active Ingredient	Measurement
Copper hydroxide† (CAS# 20427-59-2)	19.6%
Other Ingredients	80.4%

†Metallic Copper equivalent 12.8%

### Coverage

- 5,500 sq/ft (approx)
- 2,200 lin. ft (approx)

### Uses

- All applications using Terra-Barrier™ RB



**Packaging**

15' x 100'  
75 lbs per roll

### Installation (cont)

SpinOut® should be applied to all sheet edges in a minimum 3-inch wide band. A normal walking speed should be used during application to apply a consistent thin coat of SpinOut® all along the sheet edge. Avoid over application to the point material puddles or runs.

Minimum recommended application temperature is 50°F. Ambient conditions effect drying times– 10 min on a warm, sunny day; up to 45 min on a cool, cloudy day. SpinOut® is resistant to general weathering and UV exposure. However, re-application to laps and potentially the entire surface of the Terra-BARRIER™ RB may be required after 12 months of exposure to traffic and abrasion on those projects where the waterproofed area has been open to construction traffic.